NSN 5985-01-142-2710

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-142-2710
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
Between 2.750 inches and 2.770 inches
Overall Height:
Between 3.490 inches and 3.510 inches
Overall Width:
Between 0.550 inches and 0.570 inches
Shaft Diameter:
Between 0.250 inches and 0.260 inches
Shaft Length:
Between 0.490 inches and 0.510 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
200.0 milliwatts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+40.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
1 threaded stud
Frequency Range:
Between 7900.000 megahertz and 8400.000 megahertz
Adjustment Device Type And Quantity:
1 shaft
Shaft Type:
Round, flatted
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:

N/a

NSN 5985-01-142-2710

Variable Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0