## NSN 5985-01-143-3033

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-143-3033

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.359 inches
Overall Height:
2.078 inches
Overall Width:
1.610 inches
Voltage Standing Wave Ratio:
1.10 and 1.30
Coaxial Connector Series Designation:
Sma
Power Rating:
500.0 milliwatts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.3
Overall Attenuation Range In Decibels:
+0.0/+70.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
7
Attenuation Per Step In Decibels:
10.0
Mounting Facility Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 2.000 gigahertz
Overall Attenuation Accuracy In Decibels:
-0.20/+0.20
Adjustment Device Type And Quantity:
1 knob w/dial
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5985-01-143-3033

Variable Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A223a0