NSN 5985-01-143-9857

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-143-9857

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.300 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.140 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.800 inches
Overall Height:
0.500 inches
Overall Width:
1.900 inches
Unthreaded Mounting Hole Diameter:
0.104 inches
End Application:
An/trc-170
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Sma Insertion Loss At Minimum Attenuation In Maximum Decibels:
Insertion Loss At Minimum Attenuation In Maximum Decibels:
Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.6
Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.6 Overall Attenuation Range In Decibels:
Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.6 Overall Attenuation Range In Decibels: +0.0/+60.0
Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.6 Overall Attenuation Range In Decibels: +0.0/+60.0 Attenuation Variation Method:
Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.6 Overall Attenuation Range In Decibels: +0.0/+60.0 Attenuation Variation Method: Continuous
Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.6 Overall Attenuation Range In Decibels: +0.0/+60.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity:
Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.6 Overall Attenuation Range In Decibels: +0.0/+60.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole
Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.6 Overall Attenuation Range In Decibels: +0.0/+60.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole Frequency Range:
Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.6 Overall Attenuation Range In Decibels: +0.0/+60.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole Frequency Range: Between 4.400 gigahertz and 5.000 gigahertz
Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.6 Overall Attenuation Range In Decibels: +0.0/+60.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole Frequency Range: Between 4.400 gigahertz and 5.000 gigahertz Overall Attenuation Accuracy In Decibels:
Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.6 Overall Attenuation Range In Decibels: +0.0/+60.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole Frequency Range: Between 4.400 gigahertz and 5.000 gigahertz Overall Attenuation Accuracy In Decibels: -1.00/+1.00
Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.6 Overall Attenuation Range In Decibels: +0.0/+60.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole Frequency Range: Between 4.400 gigahertz and 5.000 gigahertz Overall Attenuation Accuracy In Decibels: -1.00/+1.00 Adjustment Device Type And Quantity:
Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.6 Overall Attenuation Range In Decibels: +0.0/+60.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole Frequency Range: Between 4.400 gigahertz and 5.000 gigahertz Overall Attenuation Accuracy In Decibels: -1.00/+1.00 Adjustment Device Type And Quantity: 1 electronic, voltage controlled
Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.6 Overall Attenuation Range In Decibels: +0.0/+60.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole Frequency Range: Between 4.400 gigahertz and 5.000 gigahertz Overall Attenuation Accuracy In Decibels: -1.00/+1.00 Adjustment Device Type And Quantity: 1 electronic, voltage controlled Mounting Facility Pattern:
Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.6 Overall Attenuation Range In Decibels: +0.0/+60.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole Frequency Range: Between 4.400 gigahertz and 5.000 gigahertz Overall Attenuation Accuracy In Decibels: -1.00/+1.00 Adjustment Device Type And Quantity: 1 electronic, voltage controlled Mounting Facility Pattern: Two position diagonal

Terminal Type And Quantity:

2 connector, coaxial, female and 3 solder stud

NSN 5985-01-143-9857

Variable Attenuator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0