## NSN 5985-01-144-5505

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-144-5505

Application	Design:

Transmission line

**Body Material:** 

Steel, stainless

Body Style:

Err-090

#### **Body Surface Treatment:**

Passivated

#### **Overall Length:**

1.200 inches

#### **Overall Diameter:**

0.360 inches

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Voltage Standing Wave Ratio:

## 1.15 and 1.20 and 1.25

## Input Impedance Rating In Ohms:

50.0

## **Output Impedance Rating In Ohms:**

50.0

#### **Coaxial Connector Series Designation:**

Sma and wpm

#### **Power Rating:**

2.0 watts average and 500.0 watts peak

#### **Rf Signal Attenuation In Decibels:**

1.0

#### Voltage Standing Wave Ratio Frequency Range:

+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz

## Attenuation Accuracy Reference Frequency:

12.4 gigahertz

#### Attenuation Accuracy In Decibels:

-0.30/+0.30

#### Unpackaged Unit Weight:

0.350 ounces

#### **Mounting Method:**

Connector

#### **Terminal Type And Quantity:**

2 connector

#### Frequency Range:

Between 0.000 hertz and 12.400 gigahertz

#### **Fsc Application Data:**

Antennas, waveguides, and related equpment

# NSN 5985-01-144-5505

Fixed Attenuator - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000

