NSN 5985-01-144-6532

Fixed Attenuator - Page 1 of 2

Application Design:



View Online at https://aerobasegroup.com/nsn/5985-01-144-6532

Body Material:
Steel, corrosion resisting
Body Style:
1b round, terminal/terminals in opposite surface
Terminal Material:
Steel, corrosion resisting
Terminal Surface Treatment:
Any acceptable
Body Surface Treatment:
Any acceptable
Overall Length:
1.000 inches
Overall Diameter:
0.375 inches
Operating Tempurature Range:
-40.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.07
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
Output Impedance Rating In Ohms: 50.0
50.0
50.0 Coaxial Connector Series Designation:
50.0 Coaxial Connector Series Designation: Sma
50.0 Coaxial Connector Series Designation: Sma Power Rating:
50.0 Coaxial Connector Series Designation: Sma Power Rating: 2.0 watts peak
50.0 Coaxial Connector Series Designation: Sma Power Rating: 2.0 watts peak Rf Signal Attenuation In Decibels:
50.0 Coaxial Connector Series Designation: Sma Power Rating: 2.0 watts peak Rf Signal Attenuation In Decibels: 6.0
Coaxial Connector Series Designation: Sma Power Rating: 2.0 watts peak Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range:
Coaxial Connector Series Designation: Sma Power Rating: 2.0 watts peak Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz
Coaxial Connector Series Designation: Sma Power Rating: 2.0 watts peak Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy In Decibels:
Coaxial Connector Series Designation: Sma Power Rating: 2.0 watts peak Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy In Decibels: -0.30/+0.30
Coaxial Connector Series Designation: Sma Power Rating: 2.0 watts peak Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy In Decibels: -0.30/+0.30 Connection Type Per Function:
Coaxial Connector Series Designation: Sma Power Rating: 2.0 watts peak Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy In Decibels: -0.30/+0.30 Connection Type Per Function: Female input and male output
Coaxial Connector Series Designation: Sma Power Rating: 2.0 watts peak Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy In Decibels: -0.30/+0.30 Connection Type Per Function: Female input and male output Mounting Method:
Coaxial Connector Series Designation: Sma Power Rating: 2.0 watts peak Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy In Decibels: -0.30/+0.30 Connection Type Per Function: Female input and male output Mounting Method: Connector
Coaxial Connector Series Designation: Sma Power Rating: 2.0 watts peak Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy In Decibels: -0.30/+0.30 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity:
Coaxial Connector Series Designation: Sma Power Rating: 2.0 watts peak Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy In Decibels: -0.30/+0.30 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector

NSN 5985-01-144-6532

Fixed Attenuator - Page 2 of 2



Fsc Application Data	Fsc	Ap	plic	ation	Data
----------------------	-----	----	------	-------	------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000