

View Online at <https://aerobasegroup.com/nsn/5985-01-145-4673>

**Application Design:**

Transmission line

**Body Material:**

Metal

**Body Style:**

1b round, terminal/terminals in opposite surface

**Body Surface Treatment:**

Any acceptable

**Overall Length:**

1.240 inches

**Overall Diameter:**

Between 0.350 inches and 0.385 inches

**Operating Temperature Range:**

-65.0 to 105.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.15 and 1.20 and 1.25 and 1.35

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

2.0 watts average and 0.5 kilowatts peak

**Rf Signal Attenuation In Decibels:**

3.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0 to 4.0 gigahertz and +4.0 to 8.0 gigahertz and +8.0 to 12.4 gigahertz and +12.4 to 18.0 gigahertz

**Attenuation Accuracy In Decibels:**

-0.30 to 0.30

**Connection Type Per Function:**

Female input and male output

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 hertz and 18.000 gigahertz

**Special Features:**

Suffix s on part number requires screening

**Test Data Document:**

81349-mil-dtl-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A20000