

View Online at <https://aerobasegroup.com/nsn/5985-01-148-0360>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

End Application:

5840-01-065-1678, radar set, an/gpn-22

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.256 inches second flange

Flange Inside Height:

0.631 inches second flange

Flange Outside Width:

1.875 inches second flange

Flange Outside Height:

1.875 inches second flange

Flange Inside Diameter:

1.625 inches first flange

Flange Depth:

0.625 inches first flange

Flange Connecting Hole Diameter:

0.172 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.02

Maximum Operating Pressure:

25.0 pounds per square inch gage

Waveguide Outside Width:

1.250 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

1.122 inches

Waveguide Inside Height:

0.497 inches

Waveguide Outside Height:

0.625 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

Waveguide Length:

10.250 inches

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy 6061 single tubing segment and flange

Surface Treatment:

Passivate single tubing segment and flange all surfaces and primer single tubing segment and flange all surfaces and paint single tubing segment and flange all surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc first flange single connection facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0