NSN 5985-01-148-0360

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-148-0360

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

End Application:

5840-01-065-1678, radar set, an/gpn-22

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.256 inches second flange

Flange Inside Height:

0.631 inches second flange

Flange Outside Width:

1.875 inches second flange

Flange Outside Height:

1.875 inches second flange

Flange Inside Diameter:

1.625 inches first flange

Flange Depth:

0.625 inches first flange

Flange Connecting Hole Diameter:

0.172 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.02

Maximum Operating Pressure:

25.0 pounds per square inch gage

Waveguide Outside Width:

1.250 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

1.122 inches

Waveguide Inside Height:

0.497 inches

Waveguide Outside Height:

0.625 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

NSN 5985-01-148-0360

Waveguide Assembly - Page 2 of 2



Flange Style: Cover type second flange Waveguide Length: 10.250 inches Flexibility: Rigid single tubing segment Material: Aluminum alloy 6061 single tubing segment and flange Surface Treatment: Passivate single tubing segment and flange all surfaces and primer single tubing segment and flange all surfaces and paint single tubing segment and flange all surfaces Style Designator: Straight type **Thread Series Designator:** Unc first flange single connection facility Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** Yes - demil/mli Fiig: A073a0