# NSN 5985-01-150-0756

Waveguide Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-150-0756

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

#### **Thread Class:**

2b first flange single connection facility

#### **Thread Direction:**

Right-hand first flange single connection facility

## **Tubing Wall Construction Style:**

Seamless single tubing segment

## Flange Quantity:

2

#### Flange Inside Width:

1.118 inches second flange and 1.126 inches second flange

#### Flange Inside Height:

0.493 inches first flange and 0.501 inches first flange

#### Flange Outside Width:

1.860 inches first flange and 1.890 inches first flange

## Flange Outside Height:

1.870 inches second flange and 1.880 inches second flange

## Flange Inside Diameter:

1.610 inches first flange and 1.640 inches first flange

## Flange Depth:

0.610 inches first flange and 0.640 inches first flange

#### Flange Connecting Hole Diameter:

1.670 inches second flange single connection facility and 1.710 inches second flange single connection facility

## **Voltage Standing Wave Ratio:**

1.05

## **Insertion Loss In Decibels:**

0.01

#### Adapter Length:

Between 1.682 inches and 1.692 inches

## Thready Qty Per Inch (tpi):

32 first flange single connection facility

## **Maximum Operating Pressure:**

15.0 pounds per square inch gage

## **Waveguide Outside Width:**

1.250 inches

#### **Thread Size:**

0.164 inches first flange single connection facility

## **Waveguide Inside Width:**

1.122 inches

## **Waveguide Inside Height:**

0.497 inches

# NSN 5985-01-150-0756

Waveguide Adapter - Page 2 of 2



# **Waveguide Outside Height:** 0.625 inches Flange Connecting Facility And Quantity: 4 unthreaded hole second flange single connection facility Flange Style: Cover type second flange **Special Features:** Special flange with six 8-32unf threaded holes Material: Aluminum alloy single tubing segment and flange **Surface Treatment:** Chromate single tubing segment and flange outside surfaces **Style Designator:** Waveguide to waveguide **Thread Series Designator:** Unc first flange single connection facility **Fsc Application Data:** Radar equipment Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A073a0