NSN 5985-01-150-1666

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-150-1666 **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** Err-090 **Body Surface Treatment:** Passivated **Overall Length:** 0.750 inches **Overall Diameter:** 0.312 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.15 and 1.25 and 1.50 and 1.80 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 2.0 watts average **Rf Signal Attenuation In Decibels:** 2.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+4.0 gigahertz and +4.1/+12.0 gigahertz and +12.1/+15.0 gigahertz and +15.1/+18.0 gigahertz **Connection Type Per Function:** Female input and male output **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz **Precious Material And Location:** Pin surface gold **Precious Material:** Gold

N/a

Shelf Life:

NSN 5985-01-150-1666

Fixed Attenuator - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A20000