# NSN 5985-01-150-6323

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-150-6323

# Application Design:

Transmission line

### Body Style:

Irregular

## Overall Length:

2.000 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

1.836 inches

## Center To Center Distance Between Mounting Facilities Parallel To Width:

1.336 inches

## **Overall Height:**

0.750 inches

# Overall Width:

1.900 inches

## Unthreaded Mounting Hole Diameter:

0.093 inches

# Voltage Standing Wave Ratio:

1.25 and 1.35 and 1.50

# **Coaxial Connector Series Designation:**

Sma

#### Insertion Loss At Minimum Attenuation In Maximum Decibels:

3.0

#### **Overall Attenuation Range In Decibels:**

+0.0/+38.0

#### **Attenuation Variation Method:**

Continuous

#### Mounting Facility Type And Quantity:

4 unthreaded hole

# Frequency Range:

Between 20.000 megahertz and 500.000 megahertz

# Adjustment Device Type And Quantity:

1 electronic, voltage controlled

# Mounting Facility Pattern:

Four position rectangular

# Impedance Rating In Ohms:

50.0 input-output

# Terminal Type And Quantity:

2 connector, coaxial, female and 4 solder stud

Shelf Life:

N/a

### Unit Of Measure:

---

# NSN 5985-01-150-6323

Variable Attenuator - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A223a0

