NSN 5985-01-153-0314

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-153-0314 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Rectangular terminal/terminals on three surfaces **Terminal Material:** Copper **Terminal Surface Treatment:** Gold plated **Body Surface Treatment:** Painted **Overall Length:** 0.647 inches **Overall Height:** 0.035 inches **Overall Width:** 0.374 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.30 **Input Impedance Rating In Ohms:** 50.0 **Output Impedance Rating In Ohms:** 50.0 **Power Rating:** 100.0 watts peak Rf Signal Attenuation In Decibels: 1.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+12.0 gigahertz **Attenuation Accuracy In Decibels:** -0.50/+0.50 **Unpackaged Unit Weight:** 0.003 pounds **Mounting Method: Terminal Terminal Type And Quantity:** Ribbon3

Frequency Range:
Between 0.000 hertz and 12.000 gigahertz

NSN 5985-01-153-0314

Fixed Attenuator - Page 2 of 2



Draai	aua N	// ntori	ial And	d Location:
rieci	ous n	nateri	ıaı Aliu	a Localion.

Terminal and contact surfaces gold and contact surfaces platinum

Precious Material:

Gold and platinum

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000