

View Online at <https://aerobasegroup.com/nsn/5985-01-153-9430>

**Application Design:**

Transmission line

**Body Material:**

Beryllium copper

**Body Style:**

1b round, terminal/terminals in opposite surface

**Body Surface Treatment:**

Any acceptable

**Overall Length:**

4.375 inches

**Overall Diameter:**

0.760 inches

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**End Application:**

An/fps-117

**Voltage Standing Wave Ratio:**

1.20

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

N

**Power Rating:**

2.0 watts average and 2.0 kilowatts peak

**Rf Signal Attenuation In Decibels:**

2.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0/+3.0 gigahertz

**Attenuation Accuracy In Decibels:**

-0.20/+0.20

**Connection Type Per Function:**

Female input and male output

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 hertz and 3.000 gigahertz

**Test Data Document:**

81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A20000