## NSN 5985-01-154-2517

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-154-2517

Application Design:
Transmission line
Body Material:
Metal
Body Style:
Rectangular terminal/terminals on three surfaces
Terminal Material:
Copper
Terminal Surface Treatment:
Any acceptable
Body Surface Treatment:
Any acceptable
Overall Length:
0.730 inches
Overall Height:
0.035 inches
Overall Width:
0.480 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
30.0
Output Impedance Rating In Ohms:
Output Impedance Rating In Ohms:
Output Impedance Rating In Ohms: 50.0
Output Impedance Rating In Ohms: 50.0 Power Rating:
Output Impedance Rating In Ohms: 50.0 Power Rating: 1.0 watts average
Output Impedance Rating In Ohms: 50.0  Power Rating: 1.0 watts average  Rf Signal Attenuation In Decibels:
Output Impedance Rating In Ohms: 50.0  Power Rating: 1.0 watts average  Rf Signal Attenuation In Decibels: 6.0
Output Impedance Rating In Ohms: 50.0  Power Rating: 1.0 watts average Rf Signal Attenuation In Decibels: 6.0  Voltage Standing Wave Ratio Frequency Range:
Output Impedance Rating In Ohms: 50.0  Power Rating: 1.0 watts average  Rf Signal Attenuation In Decibels: 6.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+1.0 gigahertz
Output Impedance Rating In Ohms: 50.0  Power Rating: 1.0 watts average Rf Signal Attenuation In Decibels: 6.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+1.0 gigahertz  Attenuation Accuracy Reference Frequency:
Output Impedance Rating In Ohms: 50.0  Power Rating: 1.0 watts average Rf Signal Attenuation In Decibels: 6.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+1.0 gigahertz  Attenuation Accuracy Reference Frequency: 1.0 gigahertz
Output Impedance Rating In Ohms: 50.0  Power Rating: 1.0 watts average Rf Signal Attenuation In Decibels: 6.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+1.0 gigahertz  Attenuation Accuracy Reference Frequency: 1.0 gigahertz  Attenuation Accuracy In Decibels:
Output Impedance Rating In Ohms: 50.0  Power Rating: 1.0 watts average Rf Signal Attenuation In Decibels: 6.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+1.0 gigahertz  Attenuation Accuracy Reference Frequency: 1.0 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50
Output Impedance Rating In Ohms: 50.0  Power Rating: 1.0 watts average Rf Signal Attenuation In Decibels: 6.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+1.0 gigahertz  Attenuation Accuracy Reference Frequency: 1.0 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50  Mounting Method:
Output Impedance Rating In Ohms: 50.0  Power Rating: 1.0 watts average Rf Signal Attenuation In Decibels: 6.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+1.0 gigahertz  Attenuation Accuracy Reference Frequency: 1.0 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50  Mounting Method: Terminal
Output Impedance Rating In Ohms: 50.0  Power Rating: 1.0 watts average Rf Signal Attenuation In Decibels: 6.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+1.0 gigahertz  Attenuation Accuracy Reference Frequency: 1.0 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50  Mounting Method: Terminal Terminal Type And Quantity:

## NSN 5985-01-154-2517

Fixed Attenuator - Page 2 of 2



Fsc Application Data	Fsc Appl	ication	Data
----------------------	----------	---------	------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000