NSN 5985-01-155-1375

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-155-1375

View Online at https://aerobasegroup.com/nsn/5985-01-155-1375
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
1.630 inches
Overall Height:
1.503 inches
Overall Width:
1.090 inches
Shaft Length:
0.125 inches
Unthreaded Mounting Hole Diameter:
0.144 inches
Distance Between Mounting Facility Centers:
1.094 inches
End Application:
5840-01-141-4378
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
500.0 milliwatts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
1.5
Overall Attenuation Range In Decibels:
+0.0/+15.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
1 bracket and 2 unthreaded hole
Frequency Range:
Between 0.000 hertz and 200.000 megahertz
Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:
Two position in-line
Shaft Type:
Round, slotted
Impedance Rating In Ohms:
50.0 input-output

NSN 5985-01-155-1375

Variable Attenuator - Page 2 of 2



Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A223a0