

View Online at <https://aerobasegroup.com/nsn/5985-01-155-1376>

**Application Design:**

Printed circuit board

**Body Style:**

Irregular

**Overall Length:**

3.310 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.700 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.200 inches

**Overall Height:**

0.675 inches

**Overall Width:**

2.310 inches

**Voltage Standing Wave Ratio:**

1.50

**Mounting Facility Screw Thread Series Designator:**

Unc

**Insertion Loss At Minimum Attenuation In Maximum Decibels:**

3.0

**Overall Attenuation Range In Decibels:**

+10.0/+50.0

**Attenuation Variation Method:**

Stepped

**Step Position Quantity:**

3

**Attenuation Per Step In Decibels:**

10.0 and 20.0 and 20.0

**Mounting Facility Type And Quantity:**

4 threaded hole

**Frequency Range:**

Between 2.000 megahertz and 30.000 megahertz

**Overall Attenuation Accuracy In Decibels:**

-0.50/+0.50

**Mounting Thread Quantity:**

40 per inch

**Adjustment Device Type And Quantity:**

1 electronic, programmable

**Mounting Facility Pattern:**

Four position rectangular

**Mounting Facility Screw Thread Diameter:**

0.112 inches

**Impedance Rating In Ohms:**

50.0 input-output

**Terminal Type And Quantity:**

12 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A223a0