

View Online at <https://aerobasegroup.com/nsn/5985-01-155-1376>

Application Design:

Printed circuit board

Body Style:

Irregular

Overall Length:

3.310 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.700 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.200 inches

Overall Height:

0.675 inches

Overall Width:

2.310 inches

Voltage Standing Wave Ratio:

1.50

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

3.0

Overall Attenuation Range In Decibels:

+10.0/+50.0

Attenuation Variation Method:

Stepped

Step Position Quantity:

3

Attenuation Per Step In Decibels:

10.0 and 20.0 and 20.0

Mounting Facility Type And Quantity:

4 threaded hole

Frequency Range:

Between 2.000 megahertz and 30.000 megahertz

Overall Attenuation Accuracy In Decibels:

-0.50/+0.50

Mounting Thread Quantity:

40 per inch

Adjustment Device Type And Quantity:

1 electronic, programmable

Mounting Facility Pattern:

Four position rectangular

Mounting Facility Screw Thread Diameter:

0.112 inches

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

12 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0