## NSN 5985-01-155-1377

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-155-1377

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.400 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.750 inches
Overall Height:
1.620 inches
Overall Width:
1.310 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.750 inches
End Application:
4920-01-126-6887
Voltage Standing Wave Ratio:
1.30
Coaxial Connector Series Designation:
Sma
Power Rating:
3.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.2
Overall Attenuation Range In Decibels:
+0.0/+10.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 0.000 hertz and 2.000 gigahertz
Overall Attenuation Accuracy In Decibels:
-0.20/+0.20
Mounting Thread Quantity:

32 per inch

## NSN 5985-01-155-1377

Variable Attenuator - Page 2 of 2



## **Adjustment Device Type And Quantity:**

1 knob

**Mounting Facility Pattern:** 

Four position diamond

**Mounting Facility Screw Thread Diameter:** 

0.138 inches

**Terminal Type And Quantity:** 

2 connector, coaxial, female

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0