NSN 5985-01-155-1378

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-155-1378

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

3.400 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches

Overall Height:

1.620 inches

Overall Width:

1.310 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.750 inches

End Application:

4920-01-126-6887

Voltage Standing Wave Ratio:

1.30

Coaxial Connector Series Designation:

Sma

Power Rating:

3.0 watts average

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.2

Overall Attenuation Range In Decibels:

+0.0/+60.0

Attenuation Variation Method:

Stepped

Step Position Quantity:

6

Attenuation Per Step In Decibels:

10.0

Mounting Facility Type And Quantity:

4 threaded hole

Frequency Range:

Between 0.000 hertz and 2.000 gigahertz

Mounting Thread Quantity:

32 per inch

Adjustment Device Type And Quantity:

1 knob

NSN 5985-01-155-1378

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern:

Four position diamond

Mounting Facility Screw Thread Diameter:

0.138 inches

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A223a0