# NSN 5985-01-155-9601

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-155-9601

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

## Thread Class:

2b first flange all connection facilities

## **Thread Direction:**

Right-hand first flange all connection facilities

#### **End Application:**

Radar set an/tpn-22

#### **Tubing Wall Construction Style:**

Corrugated single tubing segment

## Flange Quantity:

2

#### Flange Inside Width:

1.253 inches second flange and 1.256 inches second flange

#### Flange Inside Height:

0.628 inches second flange and 0.631 inches second flange

#### Flange Outside Width:

1.860 inches second flange and 1.890 inches second flange

#### Flange Outside Height:

1.860 inches second flange and 1.890 inches second flange

## Flange Depth:

0.610 inches first flange and 0.640 inches first flange

## Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities and 0.172 inches second flange all connection facilities

## Voltage Standing Wave Ratio:

```
1.10
```

Insertion Loss In Decibels:

0.12

Maximum Operating Pressure:

30.0 pounds per square inch gage

#### Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

#### **Thread Size:**

0.164 inches first flange all connection facilities

#### Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

## Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

## Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

## Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

## NSN 5985-01-155-9601

Waveguide Assembly - Page 2 of 2



Flange Style: Cover type second flange Waveguide Length: Between 47.750 inches and 48.250 inches **Special Features:** Silicon rubber jacket for waveguide Flexibility: Flexible single tubing segment Material: Rubber single tubing jacket **Precious Material And Location:** tubing segment surfaces silver **Precious Material:** Silver Surface Treatment: Silver single tubing segment all surfaces **Style Designator:** Straight type **Thread Series Designator:** Unc first flange all connection facilities **Fsc Application Data:** Antennas, waveguides, and related equipment Shelf Life: Unit Of Measure: Demilitarization: Fiig: A073a0

N/a

---

No