NSN 5985-01-156-8844

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-156-8844

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Passivated
Overall Length:
2.280 inches
Overall Diameter:
0.840 inches
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.25
Input Impedance Rating In Ohms:
93.0
Output Impedance Rating In Ohms:
93.0
Coaxial Connector Series Designation:
Ν
Power Rating:
-
0.3 kilowatts peak
-
0.3 kilowatts peak
0.3 kilowatts peak Rf Signal Attenuation In Decibels:
0.3 kilowatts peak Rf Signal Attenuation In Decibels: 30.0
0.3 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range:
0.3 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.4 gigahertz
0.3 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.4 gigahertz Attenuation Accuracy In Decibels:
0.3 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75
0.3 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Connection Type Per Function:
0.3 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Connection Type Per Function: Female output and male input
0.3 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Connection Type Per Function: Female output and male input Mounting Method:
0.3 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Connection Type Per Function: Female output and male input Mounting Method: Connector
0.3 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Connection Type Per Function: Female output and male input Mounting Method: Connector Terminal Type And Quantity:
0.3 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Connection Type Per Function: Female output and male input Mounting Method: Connector Terminal Type And Quantity: 2 connector
0.3 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Connection Type Per Function: Female output and male input Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:
0.3 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Connection Type Per Function: Female output and male input Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz

NSN 5985-01-156-8844

Fixed Attenuator - Page 2 of 2

Demilitarization:

No

Fiig:

A20000

