NSN 5985-01-156-9097

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-156-9097

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

3.640 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches

Overall Height:

2.380 inches

Overall Width:

0.880 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.375 inches

Voltage Standing Wave Ratio:

1.50

Coaxial Connector Series Designation:

Sma

Power Rating:

1.0 watts average and 150.0 watts peak

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.2

Overall Attenuation Range In Decibels:

+0.0/+3.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

4 threaded hole

Frequency Range:

Between 0.960 gigahertz and 1.215 gigahertz

Mounting Thread Quantity:

40 per inch

Adjustment Device Type And Quantity:

1 shaft

Mounting Facility Pattern:

Four position rectangular

NSN 5985-01-156-9097

Variable Attenuator - Page 2 of 2

Shaft Type:

Round, slotted

Mounting Facility Screw Thread Diameter:

0.112 inches

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A223a0

