NSN 5985-01-156-9097

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-156-9097

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.640 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.375 inches
Overall Height:
2.380 inches
Overall Width:
0.880 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.375 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average and 150.0 watts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.2
Overall Attenuation Range In Decibels:
+0.0/+3.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 0.960 gigahertz and 1.215 gigahertz
Mounting Thread Quantity:
40 per inch
Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:

Four position rectangular

NSN 5985-01-156-9097

Variable Attenuator - Page 2 of 2



Shaft Type:
Round, slotted
Mounting Facility Screw Thread Diameter:
0.112 inches
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A223a0