## NSN 5985-01-157-7868

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:



View Online at https://aerobasegroup.com/nsn/5985-01-157-7868

Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Passivated
Overall Length:
0.880 inches
Overall Diameter:
0.385 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average and 100.0 watts peak
Rf Signal Attenuation In Decibels:
3.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+18.0 gigahertz
Attenuation Accuracy Reference Frequency:
18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Connection Type Per Function:
Female output and male input
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Shelf Life:
N/a

## NSN 5985-01-157-7868

Fixed Attenuator - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A20000