NSN 5985-01-157-7870

Fixed Attenuator - Page 1 of 2

Application Design: Transmission line



View Online at https://aerobasegroup.com/nsn/5985-01-157-7870

Body Material:
Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Passivated
Overall Length:
0.880 inches
Overall Diameter:
0.385 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average and 100.0 watts peak
Rf Signal Attenuation In Decibels:
10.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+18.0 gigahertz
Attenuation Accuracy Reference Frequency:
18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Connection Type Per Function:
Female output and male input
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Shelf Life:
N/a

NSN 5985-01-157-7870

Fixed Attenuator - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000