# NSN 5985-01-158-7229

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-158-7229

## Application Design:

Transmission line

### **Body Material:**

Brass

#### Body Style:

Rectangular terminal/terminals on opposite surfaces

#### **Terminal Material:**

Brass

#### **Terminal Surface Treatment:**

Gold plated

#### **Body Surface Treatment:**

Gold plated

#### Overall Length:

Between 0.748 inches and 0.755 inches

#### **Overall Height:**

Between 0.246 inches and 0.265 inches

#### **Overall Width:**

Between 0.248 inches and 0.255 inches

#### Operating Tempurature Range:

-54.0/+71.0 degrees celsius

### Voltage Standing Wave Ratio:

1.20 and 1.40

## Input Impedance Rating In Ohms:

50.0

#### **Output Impedance Rating In Ohms:**

50.0

#### **Power Rating:**

1.0 watts average

#### **Rf Signal Attenuation In Decibels:**

20.0

## Voltage Standing Wave Ratio Frequency Range:

+0.0/+8.0 gigahertz and +8.0/+12.0 gigahertz

## Attenuation Accuracy Reference Frequency:

1.0 gigahertz

## Attenuation Accuracy In Decibels:

-0.50/+0.50

## Unpackaged Unit Weight:

0.003 pounds

## Mounting Method:

Terminal

## Terminal Type And Quantity:

2 ribbon

## NSN 5985-01-158-7229

Fixed Attenuator - Page 2 of 2



Frequency Range:

Between 0.000 hertz and 12.000 gigahertz

#### Precious Material And Location:

Body surface gold

Precious Material:

Gold

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A20000