NSN 5985-01-158-9894

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-158-9894

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.510 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.750 inches
Overall Height:
1.480 inches
Overall Width:
2.310 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.880 inches
End Application:
An/fps-117
Voltage Standing Wave Ratio:
1.30
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
1.1
1.1 Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels: +0.0/+12.0
Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Variation Method:
Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Variation Method: Continuous
Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity:
Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole
Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range:
Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 63.750 megahertz and 86.250 megahertz
Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 63.750 megahertz and 86.250 megahertz Mounting Thread Quantity:
Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 63.750 megahertz and 86.250 megahertz Mounting Thread Quantity: 40 per inch
Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 63.750 megahertz and 86.250 megahertz Mounting Thread Quantity: 40 per inch Adjustment Device Type And Quantity:
Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 63.750 megahertz and 86.250 megahertz Mounting Thread Quantity: 40 per inch Adjustment Device Type And Quantity: 1 slotted screw

0.112 inches

NSN 5985-01-158-9894

Variable Attenuator - Page 2 of 2



Impedance Ra	ating In	Ohms:
--------------	----------	-------

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0