NSN 5985-01-159-0718



Variable Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-159-0718 **Application Design:** Transmission line **Body Style:** Coaxial type **Overall Length:** 4.630 inches **Overall Height:** 3.940 inches **Overall Width:** Between 3.210 inches and 3.290 inches **Voltage Standing Wave Ratio:** 1.25 **Coaxial Connector Series Designation:** Sma **Power Rating:** 2.0 watts average and 200.0 kilowatts peak **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 0.4 **Overall Attenuation Range In Decibels:** +0.0/+49.0 **Attenuation Accuracy Reference Frequency:** 77.0 megahertz **Attenuation Variation Method:** Stepped **Step Position Quantity:** 49 **Attenuation Per Step In Decibels:** Frequency Range: Between 63.000 megahertz and 77.000 megahertz **Overall Attenuation Accuracy In Decibels:** -0.20/+0.20

Adjustment Device Type And Quantity:

2 knob w/dial

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

NSN 5985-01-159-0718

Variable Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0