NSN 5985-01-159-3816

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:



View Online at https://aerobasegroup.com/nsn/5985-01-159-3816

Err-090							
Body Surface Treatment:							
Passivated							
Overall Length:							
0.880 inches							
Overall Diameter:							
0.385 inches							
Operating Tempurature Range:							
-55.0/+125.0 degrees celsius							
Voltage Standing Wave Ratio:							
1.15 and 1.35							
Input Impedance Rating In Ohms:							
50.0							
Output Impedance Rating In Ohms:							
50.0							
Coaxial Connector Series Designation:							
Sma							
Power Rating:							
2.0 watts average and 100.0 kilowatts peak							
Rf Signal Attenuation In Decibels:							
1.0							
Voltage Standing Wave Ratio Frequency Range:							
+0.0/+18.0 gigahertz							
Attenuation Accuracy Reference Frequency:							
18.0 gigahertz							
Attenuation Accuracy In Decibels:							
-0.30/+0.30							
Connection Type Per Function:							
Female output and male input							
Mounting Method:							
Terminal							
Terminal Type And Quantity:							
2 connector							
Frequency Range:							
Between 0.000 hertz and 18.000 gigahertz							
Shelf Life:							
N/a							

NSN 5985-01-159-3816

Fixed Attenuator - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000