NSN 5985-01-159-5157

Fixed Attenuator - Page 1 of 2

Female output and male input



View Online at https://aerobasegroup.com/nsn/5985-01-159-5157

Application Design:
Transmission line
Body Material:
Any acceptable
Body Style:
Rectangular, terminal/terminals on opposite surfaces
Body Surface Treatment:
Enamel
Overall Length:
4.688 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.703 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.250 inches
Overall Height:
1.250 inches
Overall Width:
1.625 inches
Mounting Hole/stud Quantity:
4
Body Length:
3.234 inches
Unthreaded Mounting Hole Diameter:
0.196 inches
Operating Tempurature Range:
-40.0/+45.0 degrees celsius
Voltage Standing Wave Ratio:
1.15
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
40.0 watts average
Rf Signal Attenuation In Decibels:
10.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+1000.0 megahertz
Connection Type Per Function:

NSN 5985-01-159-5157

Fixed Attenuator - Page 2 of 2



Mounting Method:
Unthreaded hole
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 1000.000 megahertz
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A20000