

View Online at <https://aerobasegroup.com/nsn/5985-01-159-7718>

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

3.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches

Overall Height:

0.500 inches

Overall Width:

2.000 inches

Unthreaded Mounting Hole Diameter:

0.156 inches

Voltage Standing Wave Ratio:

1.30

Coaxial Connector Series Designation:

Sma

Insertion Loss At Minimum Attenuation In Maximum Decibels:

2.5

Overall Attenuation Range In Decibels:

+0.0/+56.0

Attenuation Variation Method:

Stepped

Step Position Quantity:

2

Attenuation Per Step In Decibels:

28.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Frequency Range:

Between 250.000 megahertz and 450.000 megahertz

Overall Attenuation Accuracy In Decibels:

-0.25/+0.25

Adjustment Device Type And Quantity:

1 electronic, programmable

Mounting Facility Pattern:

Four position rectangular

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female and 6 tab, solder lug

Specification Data:

81413-201477 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A223a0