NSN 5985-01-161-3109

Fixed Attenuator - Page 1 of 2

Application Design:



View Online at https://aerobasegroup.com/nsn/5985-01-161-3109

Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Overall Length:
1.500 inches
Overall Diameter:
0.360 inches
Operating Tempurature Range:
+0.0/+60.0 degrees celsius
End Application:
5820-01-108-5279
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
Power Rating: 1.0 watts average
_
1.0 watts average
1.0 watts average Rf Signal Attenuation In Decibels:
1.0 watts average Rf Signal Attenuation In Decibels: 3.0
1.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range:
1.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +4.0/+8.5 gigahertz
1.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +4.0/+8.5 gigahertz Connection Type Per Function:
1.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +4.0/+8.5 gigahertz Connection Type Per Function: Male input and female output
1.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +4.0/+8.5 gigahertz Connection Type Per Function: Male input and female output Mounting Method:
1.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +4.0/+8.5 gigahertz Connection Type Per Function: Male input and female output Mounting Method: Connector
1.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +4.0/+8.5 gigahertz Connection Type Per Function: Male input and female output Mounting Method: Connector Terminal Type And Quantity:
1.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +4.0/+8.5 gigahertz Connection Type Per Function: Male input and female output Mounting Method: Connector Terminal Type And Quantity: 2 connector
1.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +4.0/+8.5 gigahertz Connection Type Per Function: Male input and female output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:
1.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +4.0/+8.5 gigahertz Connection Type Per Function: Male input and female output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 4.000 gigahertz and 8.500 gigahertz
1.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +4.0/+8.5 gigahertz Connection Type Per Function: Male input and female output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 4.000 gigahertz and 8.500 gigahertz Precious Material And Location:
1.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +4.0/+8.5 gigahertz Connection Type Per Function: Male input and female output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 4.000 gigahertz and 8.500 gigahertz Precious Material And Location: Connector surfaces gold Precious Material: Gold
1.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +4.0/+8.5 gigahertz Connection Type Per Function: Male input and female output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 4.000 gigahertz and 8.500 gigahertz Precious Material And Location: Connector surfaces gold Precious Material:

NSN 5985-01-161-3109

Fixed Attenuator - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A20000