

NSN 5985-01-161-3112 Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-161-3112 **Application Design:** Transmission line

Body Material: Any acceptable **Body Style:** Err-090 **Body Surface Treatment:** Silver plated **Overall Length:** 2.260 inches **Overall Diameter:** 0.560 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.25 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 5.0 watts average

Rf Signal Attenuation In Decibels:

50.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+4.0 gigahertz

Connection Type Per Function:

Female output and male input

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 4.000 gigahertz

Precious Material And Location:

Terminal and body surfaces silver

Precious Material:

Silver

Shelf Life:

N/a

NSN 5985-01-161-3112

Fixed Attenuator - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000