## NSN 5985-01-162-6373

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-162-6373

Application Design:
Transmission line
Body Style:
Irregular
Overall Length:
2.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.044 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.093 inches
Overall Height:
0.500 inches
Overall Width:
2.000 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+20.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 4.000 gigahertz and 8.000 gigahertz
Overall Attenuation Accuracy In Decibels:
-3.00/+3.00
Mounting Thread Quantity:
40 per inch
Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:
Four position rectangular

Shaft Type:

Round, slotted

## NSN 5985-01-162-6373

Variable Attenuator - Page 2 of 2



0.112 inches

**Terminal Type And Quantity:** 

2 connector, coaxial, female

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0