

View Online at <https://aerobasegroup.com/nsn/5985-01-164-3471>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Bend Angle In Deg:**

90.0 single bend e-plane

**Tubing Wall Construction Style:**

Seamless all tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.620 inches second flange and 0.624 inches second flange

**Flange Inside Height:**

0.309 inches second flange and 0.313 inches second flange

**Flange Outside Width:**

1.297 inches second flange and 1.327 inches second flange

**Flange Outside Height:**

1.297 inches second flange and 1.327 inches second flange

**Flange Depth:**

0.985 inches second flange and 1.015 inches second flange

**Flange Connecting Hole Diameter:**

0.144 inches second flange all connection facilities and 0.147 inches second flange all connection facilities

**Voltage Standing Wave Ratio:**

1.10

**Insertion Loss In Decibels:**

0.10

**Maximum Operating Pressure:**

10.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 0.699 inches and 0.705 inches

**Waveguide Inside Width:**

Between 0.6195 inches and 0.6245 inches

**Waveguide Inside Height:**

Between 0.3085 inches and 0.3135 inches

**Waveguide Outside Height:**

Between 0.388 inches and 0.394 inches

**Waveguide Longer Offset Distance:**

4.100 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole second flange all connection facilities

**Flange Style:**

Cover type second flange

**Waveguide Offset Distance:**

1.150 inches

**Flexibility:**

Rigid third tubing segment

**Material:**

Copper alloy all flange

**Surface Treatment:**

Primer all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces

**Style Designator:**

Bend type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0