NSN 5985-01-165-1660

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-165-1660

Application Design:
Transmission line
Body Style:
Irregular
Overall Length:
1.440 inches
Overall Height:
0.810 inches
Overall Width:
1.090 inches
Unthreaded Mounting Hole Diameter:
0.144 inches
Distance Between Mounting Facility Centers:
0.547 inches
Voltage Standing Wave Ratio:
2.00
Coaxial Connector Series Designation:
Sma
Power Rating:
0.5 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
2.0
Overall Attenuation Range In Decibels:
+0.0/+10.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
2 unthreaded hole
Frequency Range:
Between 0.000 hertz and 400.000 megahertz
Overall Attenuation Accuracy In Decibels:
-1.00/+1.00
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Two position in-line
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:

N/a

NSN 5985-01-165-1660

Variable Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0