## NSN 5985-01-166-3733

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-166-3733
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
Between 2.719 inches and 2.781 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.375 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.125 inches
Overall Height:
Between 0.906 inches and 0.968 inches
Overall Width:
Between 2.282 inches and 2.404 inches
Voltage Standing Wave Ratio:
1.20
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+30.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
3
Attenuation Per Step In Decibels:
10.0
Mounting Facility Type And Quantity:
4 flange w/mounting hole
Frequency Range:
Between 0.000 megahertz and 1000.000 megahertz
Overall Attenuation Accuracy In Decibels:
-1.00/+1.00
Adjustment Device Type And Quantity:
1 electronic, programmable
Mounting Facility Pattern:
Four position rectangular
Impedance Rating In Ohms:

50.0 input-output

## NSN 5985-01-166-3733

Variable Attenuator - Page 2 of 2



Terminal Type And Quanti	ty	:
--------------------------	----	---

2 connector, coaxial, female and 4 pin

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0