NSN 5985-01-166-7179

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-166-7179

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.620 inches second flange and 0.624 inches second flange

Flange Inside Height:

0.309 inches second flange and 0.313 inches second flange

Flange Outside Width:

1.298 inches second flange and 1.328 inches second flange

Flange Outside Height:

1.298 inches second flange and 1.328 inches second flange

Flange Inside Diameter:

0.985 inches first flange and 1.015 inches first flange

Flange Depth:

0.360 inches first flange and 0.390 inches first flange

Flange Connecting Hole Diameter:

0.144 inches second flange all connection facilities and 0.147 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.20

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

Thread Size:

0.138 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.620 inches and 0.625 inches

Waveguide Inside Height:

Between 0.309 inches and 0.314 inches

Waveguide Outside Height:

Between 0.388 inches and 0.394 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

NSN 5985-01-166-7179

Waveguide Assembly - Page 2 of 2



Flange Style:

Cover type second flange

Waveguide Length:

Between 16.130 inches and 16.370 inches

Flexibility:

Flexible single tubing segment

Material:

Copper alloy single tubing segment

Precious Material And Location:

surfaces silver

Precious Material:

Silver

Surface Treatment:

Silver single tubing segment and flange all surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc first flange all connection facilities

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A073a0