## NSN 5985-01-167-0098

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:
Steel, stainless



View Online at https://aerobasegroup.com/nsn/5985-01-167-0098

Body Style:
1b round, terminal/terminals in opposite surface
Body Surface Treatment:
Any acceptable
Overall Length:
0.860 inches
Overall Diameter:
0.280 inches
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Rf Signal Attenuation In Decibels:
7.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+8.0 gigahertz
Attenuation Accuracy Reference Frequency:
8.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Connection Type Per Function:
Female output and male input
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 8.000 gigahertz
Specification Data:
49956-570997 manufacturers specification control

## NSN 5985-01-167-0098

Fixed Attenuator - Page 2 of 2



Fsc Application Data	Fsc Appl	ication	Data
----------------------	----------	---------	------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000