NSN 5985-01-171-6401

Fixed Attenuator - Page 1 of 2

Application Design: Transmission line



View Online at https://aerobasegroup.com/nsn/5985-01-171-6401

Body Material:
Any acceptable
Body Style:
Rectangular terminal/terminals on three surfaces
Terminal Material:
Brass
Terminal Surface Treatment:
Gold plated and platinum
Body Surface Treatment:
Any acceptable
Overall Length:
0.647 inches
Overall Height:
0.035 inches
Overall Width:
0.374 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.30
Land Charles Company Control Colors
Input Impedance Rating In Ohms:
50.0
•
50.0
50.0 Output Impedance Rating In Ohms:
50.0 Output Impedance Rating In Ohms: 50.0
50.0 Output Impedance Rating In Ohms: 50.0 Power Rating:
50.0 Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak
50.0 Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels:
50.0 Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0
50.0 Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range:
50.0 Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.0 gigahertz
Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.0 gigahertz Attenuation Accuracy In Decibels:
Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50
Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Unpackaged Unit Weight:
Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Unpackaged Unit Weight: 0.003 pounds
Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Unpackaged Unit Weight: 0.003 pounds Mounting Method:
Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Unpackaged Unit Weight: 0.003 pounds Mounting Method: Terminal
Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Unpackaged Unit Weight: 0.003 pounds Mounting Method: Terminal Terminal Type And Quantity:
Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Unpackaged Unit Weight: 0.003 pounds Mounting Method: Terminal Terminal Type And Quantity: 3 tab, solder lug

NSN 5985-01-171-6401

Fixed Attenuator - Page 2 of 2



Special	Features:
---------	-----------

Metal film element fired on tantalum nitride; alumina substrate; contact area platinum gold

Precious Material And Location:

Terminals and contact surfaces gold and contact surface platinum

Precious Material:

Gold and platinum

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000