NSN 5985-01-171-6401

Fixed Attenuator - Page 1 of 2

Application Design: Transmission line



View Online at https://aerobasegroup.com/nsn/5985-01-171-6401

| Body Material: |
|---|
| Any acceptable |
| Body Style: |
| Rectangular terminal/terminals on three surfaces |
| Terminal Material: |
| Brass |
| Terminal Surface Treatment: |
| Gold plated and platinum |
| Body Surface Treatment: |
| Any acceptable |
| Overall Length: |
| 0.647 inches |
| Overall Height: |
| 0.035 inches |
| Overall Width: |
| 0.374 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 1.30 |
| |
| Input Impedance Rating In Ohms: |
| Input Impedance Rating In Ohms: 50.0 |
| • |
| 50.0 |
| 50.0 Output Impedance Rating In Ohms: |
| 50.0 Output Impedance Rating In Ohms: 50.0 |
| 50.0 Output Impedance Rating In Ohms: 50.0 Power Rating: |
| 50.0 Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak |
| 50.0 Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: |
| 50.0 Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 |
| 50.0 Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range: |
| 50.0 Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.0 gigahertz |
| Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.0 gigahertz Attenuation Accuracy In Decibels: |
| Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 |
| Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Unpackaged Unit Weight: |
| Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Unpackaged Unit Weight: 0.003 pounds |
| Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Unpackaged Unit Weight: 0.003 pounds Mounting Method: |
| Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Unpackaged Unit Weight: 0.003 pounds Mounting Method: Terminal |
| Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Unpackaged Unit Weight: 0.003 pounds Mounting Method: Terminal Terminal Type And Quantity: |
| Output Impedance Rating In Ohms: 50.0 Power Rating: 0.5 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 5.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+12.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Unpackaged Unit Weight: 0.003 pounds Mounting Method: Terminal Terminal Type And Quantity: 3 tab, solder lug |

NSN 5985-01-171-6401

Fixed Attenuator - Page 2 of 2



| Special | Features: |
|---------|-----------|
|---------|-----------|

Metal film element fired on tantalum nitride; alumina substrate; contact area platinum gold

Precious Material And Location:

Terminals and contact surfaces gold and contact surface platinum

Precious Material:

Gold and platinum

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000