NSN 5985-01-172-4309

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-172-4309

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Bend Angle In Deg:

90.0 single bend h-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.062 inches second flange

Flange Inside Height:

0.505 inches second flange

Flange Outside Width:

1.625 inches second flange

Flange Outside Height:

1.625 inches first flange

Flange Depth:

0.438 inches second flange

Flange Connecting Hole Diameter:

0.169 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.05

Waveguide Outside Width:

1.000 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

0.900 inches

Waveguide Inside Height:

0.400 inches

Waveguide Outside Height:

0.500 inches

Waveguide Longer Offset Distance:

3.562 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

NSN 5985-01-172-4309

Waveguide Assembly - Page 2 of 2



Waveguide Offset Distance:
3.562 inches
Flexibility:
Rigid single tubing segment
Material:
Aluminum alloy single tubing segment
Surface Treatment:
Any acceptable single flange outside surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc first flange single connection facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A073a0