NSN 5985-01-172-6479



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-172-6479 **Application Design:** Transmission line **Body Material:** Metal **Body Surface Treatment:** Any acceptable **Overall Length:** 2.250 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.720 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.720 inches **Overall Width:** 0.800 inches **Mounting Hole/stud Quantity: Unthreaded Mounting Hole Diameter:** 0.120 inches **Operating Tempurature Range:** -65.0/+110.0 degrees celsius **Voltage Standing Wave Ratio:** 1.80 **Input Impedance Rating In Ohms: Output Impedance Rating In Ohms:** 300.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 100.0 milliwatts peak Rf Signal Attenuation In Decibels: **Voltage Standing Wave Ratio Frequency Range:** +8.0/+18.0 gigahertz **Connection Type Per Function:** Female output and male input **Mounting Method:** Unthreaded hole **Terminal Type And Quantity:**

2 connector

Frequency Range:

Between 8.000 gigahertz and 18.000 gigahertz

NSN 5985-01-172-6479

Fixed Attenuator - Page 2 of 2



| _ | | | | | |
|---|----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000