NSN 5985-01-172-7315

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-172-7315

view Offiline at https://derobasegroup.com/nsi//3303-01-1/2-7313
Application Design:
Transmission line
Body Style:
Irregular
Overall Length:
Between 2.480 inches and 2.540 inches
Overall Height:
0.500 inches
Overall Width:
1.945 inches
Distance Between Mounting Facility Centers:
Between 1.545 inches and 1.575 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+15.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 7.000 gigahertz and 11.000 gigahertz
Overall Attenuation Accuracy In Decibels:
-5.00/+5.00
Mounting Thread Quantity:
56 per inch
Adjustment Device Type And Quantity:
1 slotted screw
Mounting Facility Pattern:
Two position in-line
I wo position in-line Mounting Facility Screw Thread Diameter:
·

50.0 input-output

NSN 5985-01-172-7315

Variable Attenuator - Page 2 of 2



Terminal Type A	and Quantity	/ :
-----------------	--------------	------------

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0