NSN 5985-01-173-7365

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-173-7365

| Application Design: |
|--|
| Transmission line |
| Body Style: |
| Irregular |
| Overall Length: |
| 5.250 inches |
| Overall Height: |
| 0.500 inches |
| Overall Width: |
| 1.750 inches |
| Voltage Standing Wave Ratio: |
| 1.35 |
| Coaxial Connector Series Designation: |
| Sma |
| Insertion Loss At Minimum Attenuation In Maximum Decibels: |
| 3.0 |
| Overall Attenuation Range In Decibels: |
| +1.0/+63.0 |
| Attenuation Variation Method: |
| Stepped |
| Step Position Quantity: |
| 6 |
| Attenuation Per Step In Decibels: |
| 1.0 |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Frequency Range: |
| Between 20.000 megahertz and 300.000 megahertz |
| Adjustment Device Type And Quantity: |
| 1 electronic, voltage controlled |
| Mounting Facility Pattern: |
| Four position rectangular |
| Impedance Rating In Ohms: |
| 50.0 input-output |
| Terminal Type And Quantity: |
| 2 connector, coaxial, female |
| Shelf Life: |
| N/a |
| 11 1/2 04.55 |
| Unit Of Measure: |
| unit Of Measure: |

No

NSN 5985-01-173-7365

Variable Attenuator - Page 2 of 2



Fiig:

A223a0