NSN 5985-01-173-9089

Fixed Attenuator - Page 1 of 2

2 connector



View Online at https://aerobasegroup.com/nsn/5985-01-173-9089

A call call to Book to
Application Design:
Transmission line
Body Material:
Brass
Body Style:
Err-090
Body Surface Treatment:
Nickel plated
Overall Length:
1.953 inches
Overall Diameter:
0.610 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.25 and 1.30 and 1.35 and 1.40
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Tnc
Power Rating:
2.0 watts average and 500.0 watts peak
Rf Signal Attenuation In Decibels:
6.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +9.0/+12.4 gigahertz and +12.4/+15.0 gigahertz
Attenuation Accuracy Reference Frequency:
15.0 gigahertz
Attenuation Accuracy In Decibels:
-0.80/+0.80
Frequency Sensitivity Attenuation In Decibels:
0.80
Connection Type Per Function:
Female output and male input
Unpackaged Unit Weight:
4.000 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
Tommun Typo And Quantity.

NSN 5985-01-173-9089

Fixed Attenuator - Page 2 of 2



F	rea	uen	CV	Rar	าตย	9:

Between 0.000 hertz and 15.000 gigahertz

Precious Material And Location:

Contact surface gold and contact surface silver

Precious Material:

Gold and silver

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000