NSN 5985-01-174-1237

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-174-1237

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.087 inches
Bolt Circle Diameter:
1.187 inches
Overall Height:
1.577 inches
Overall Width:
1.324 inches
Voltage Standing Wave Ratio:
1.25
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average and 100.0 kilowatts peak
Mounting Facility Screw Thread Series Designator:
Unf
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.3
Overall Attenuation Range In Decibels:
+0.0/+10.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
3 threaded stud
Frequency Range:
Between 0.000 hertz and 2.000 gigahertz
Overall Attenuation Accuracy In Decibels:
-3.00/+3.00
Mounting Thread Quantity:
56 per inch
I,
Adjustment Device Type And Quantity:
Adjustment Device Type And Quantity: 1 knob w/dial

Three position circular

NSN 5985-01-174-1237

Variable Attenuator - Page 2 of 2



Mounting Facility Screw Thread Diameter: 0.086 inches

Impedance Rating In Ohms:

50.0 input-output

Precious Material And Location:

Body surface gold

Precious Material:

Gold

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0