## NSN 5985-01-174-3011

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-174-3011 **Application Design:** Audio **Body Material:** Beryllium copper **Body Style:** Rectangular terminal/terminals on three surfaces **Body Surface Treatment:** Any acceptable **Overall Length:** 0.870 inches **Overall Height:** 0.095 inches **Overall Width:** 0.500 inches **Schematic Diagram Designator: Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.30 **Input Impedance Rating In Ohms:** 50.0 **Output Impedance Rating In Ohms:** 50.0 **Power Rating:** 1.0 watts peak **Rf Signal Attenuation In Decibels: Voltage Standing Wave Ratio Frequency Range:** +0.0/+8.0 gigahertz **Attenuation Accuracy In Decibels:** -0.20/+0.20 **Mounting Method: Terminal Terminal Type And Quantity:** 3 tab, solder lug Frequency Range: Between 0.000 hertz and 8.000 gigahertz **Precious Material And Location:** Terminal surfaces gold

**Precious Material:** 

Gold

## NSN 5985-01-174-3011

Fixed Attenuator - Page 2 of 2



She	lf I	Life	е:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000