

View Online at <https://aerobasegroup.com/nsn/5985-01-175-1837>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless first tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches second flange and 1.256 inches second flange

Flange Inside Height:

0.628 inches second flange and 0.631 inches second flange

Flange Outside Width:

1.860 inches second flange and 1.890 inches second flange

Flange Outside Height:

1.860 inches second flange and 1.890 inches second flange

Flange Inside Diameter:

1.610 inches first flange and 1.640 inches first flange

Flange Depth:

0.610 inches first flange and 0.640 inches first flange

Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities and 0.172 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.10

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Thread Size:

0.164 inches first flange all connection facilities

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Length:

4.090 inches

Waveguide Center To Center Distance:

2.280 inches

Flexibility:

Rigid first tubing segment

Material:

Copper alloy all flange

Surface Treatment:

Paint all tubing segment and flange outside surfaces

Style Designator:

Offset bend type

Thread Series Designator:

Unc first flange all connection facilities

Fsc Application Data:

Antennas, waveguides and related equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A073a0