

View Online at <https://aerobasegroup.com/nsn/5985-01-175-1878>

**Application Design:**

Transmission line

**Body Style:**

Irregular

**Overall Length:**

2.500 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.844 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.175 inches

**Overall Height:**

0.500 inches

**Overall Width:**

1.625 inches

**Voltage Standing Wave Ratio:**

1.50

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

5.0 watts average and 3.0 kilowatts peak

**Mounting Facility Screw Thread Series Designator:**

Unc

**Insertion Loss At Minimum Attenuation In Maximum Decibels:**

0.5

**Overall Attenuation Range In Decibels:**

+0.0/+20.0

**Attenuation Variation Method:**

Continuous

**Mounting Facility Type And Quantity:**

4 threaded hole

**Frequency Range:**

Between 2.000 gigahertz and 2.400 gigahertz

**Overall Attenuation Accuracy In Decibels:**

-0.50/+0.50

**Mounting Thread Quantity:**

40 per inch

**Adjustment Device Type And Quantity:**

1 slotted screw

**Mounting Facility Pattern:**

Four position rectangular

**Mounting Facility Screw Thread Diameter:**

0.112 inches

**Impedance Rating In Ohms:**

50.0 input-output

**Terminal Type And Quantity:**

2 connector, coaxial, female

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A223a0